




## Rustfri stålwire

Konstruktion: 1 x 19. AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).  
10+12 mm. 1470N/mm<sup>2</sup> (150kp/mm<sup>2</sup>).

Art. No.	Min. breaking load kg	Dim. mm	Weight kg/100m
01-1051001	84	1,0	0,99
01-1051001/0,25	136	1,25-1,3	1,20
01-1051002	340	2,0	2,00
01-1051003	755	3,0	4,50
01-1051004	1.300	4,0	7,90
01-1051005	2.100	5,0	12,40
01-1051006	3.000	6,0	17,80
01-1051007	4.100	7,0	24,30
01-1051008	5.400	8,0	31,70
01-1051010	7.940	10,0	49,50
01-1051012	11.440	12,0	74,30



## Stainless steel wire rope

Construction: 1 x 19. AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).  
10+12 mm. 1470N/mm<sup>2</sup> (150kp/mm<sup>2</sup>).


Konstruktion: 7 x 7. AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).

Art. No.	Min. breaking load kg	Dim. mm	Weight kg/100m
01-1051101	57	1,0	0,41
01-1051101/0,5	92	1,5	0,90
01-1051101/0,75	180	1,8	0,99
01-1051102	230	2,0	1,40
01-1051102/0,5	370	2,5	2,70
01-1051103	515	3,0	3,10
01-1051104	915	4,0	6,10




Konstruktion: 7 x 19. AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).

Art. No.	Min. breaking load kg	Dim. mm	Weight kg/100m
01-1051203	478	3	3,42
01-1051204	850	4	6,09
01-1051205	1.320	5	9,52
01-1051206	1.910	6	13,80
01-1051208	3.390	8	24,30
01-1051210	5.310	10	38,10
01-1051212	7.640	12	54,80
01-1051214	10.400	14	77,00
01-1051216	13.600	16	97,00




Konstruktion: 6 x 36 IWRC. AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).

Art. No.	Min. breaking load kg	Dim. mm	Weight kg/100m
01-2020008	3.660	8	27
01-2020010	5.690	10	42
01-2020012	8.210	12	60,2
01-2020013	9.630	13	70,7
01-2020014	11.200	14	82,0
01-2020015	12.900	15	94,5
01-2020016	14.600	16	107
01-2020018	18.500	18	135
01-2020020	22.800	20	167
01-1051024	32.780	24	241



Konstruktion: 7 x 7 + plastikforhudning.  
AISI 316. 1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).


Art. No.	Min. breaking load kg	Dia. mm	Weight kg/100m
01-1033004	915	4-6	9,8
01-1033005	915	4-8	11,5



## PYTHON / INOX 18x7

Konstruktion: 18 x 7 AISI 316.  
1570 N/mm<sup>2</sup> (160kp/mm<sup>2</sup>).

Art. No.	Min. breaking load kN	Nom dia mm	Mass weight approx. kg/100m
01-3011504	8,70	4	6,43
01-3011505	13,28	5	10,00
01-3011506	18,99	6	14,50
01-3011506/0,5	22,27	6,5	16,40
01-3011507	26,07	7	19,70
01-3011508	34,18	8	25,70
01-3011510	53,71	10	40,20
01-3011512	77,61	12	57,90
01-3011514	104,19	14	78,80



According to EN 10264-4:2002.

Der tages forbehold for trykfejl og udgåede varer / Specifications and products are subject to change