



Løftehoved JDT TA

Produkt information

Løftehoved til tre-eller fire-parts kædesling EN 818-4.

Mærkning: I henhold til standard

Overflade: Rød malet.

Standard: EN 818-4

Sikkerhedsfaktor: 4:1.

Klasse: 8

Varenummer	Type	WLL ton	WLL 45°- 60° tons	b / b1 mm	Ø d / Ø d1	t / t1 mm	Vægt kg	Forventet levering (dage)
401100240220	TA 3/4 6	2,36	1,7	75 / 25	18 / 13	135 / 54	1,34	2
401100430220	TA 3/4 8	4,25	3	90 / 34	22 / 16	160 / 70	2,37	10
401100670220	TA 3/4 10	6,7	4,75	100 / 40	26 / 18	180 / 85	3,64	2
401101120220	TA 3/4 13	11,2	8	110 / 50	32 / 22	200 / 115	6,24	2
401101700220	TA 3/4 16	17	11,8	140 / 65	36 / 26	260 / 140	10	2
401102120220	TA 3/4 18	21,2	15	180 / 70	45 / 32	340 / 150	18,95	2
401102650220	TA 3/4 20	26,5	19	190 / 70	50 / 32	350 / 150	23,4	2
401103150220	TA 3/4 22	31,5	22,4	190 / 75	50 / 36	350 / 170	25,9	2
401104500220	TA 3/4 26	45	31,5	200 / 80	56 / 40	400 / 170	34,25	2
401105000220	TA 3/4 28	50	37,5	220 / 90	63 / 45	430 / 180	45,45	2
401106700220	TA 3/4 32	67	47,5	250 / 100	71 / 50	460 / 200	68	10
401108500220	TA 3/4 36	85	60	270 / 125	80 / 63	500 / 250	99	10
401110600220	TA 3/4 40	106	75	300 / 125	90 / 63	560 / 250	126,3	10
401113200220	TA 3/4 45	132	95	330 / 140	100 / 70	610 / 280	173,2	10

Stregtegning

