Lifting Solutions Group
Axel Johnson International

Temporary Lifeline Horizontal Skylotec L-0329

Product information



Temporary horizontal fall protection systems are very popular for assembly work in steel construction, in scaffolding and in general construction. LIFELINE HORIZONTAL is a portable, very quick to assemble and flexible fastening device. Two people can be secured over a distance of 20 metres as they work. The system's two carabiners can be attached using slings (for example) to suitable structures such as steel beams, scaffolding or concrete pillars. According to new regulatory certification requirements, the structure used must be configured for a load of 6 kN, since in the event of a fall, the force exerted on the system is limited to a maximum of 6 kN by means of damping elements.

- 20 metre horizontal range
- The structure used only needs to be able to withstand a load of 6 kN
- Flexible horizontal fall protection system for nearly every kind of construction site

... Read more

Material: Polyester, steel.
Marking: According to standard, CE-mark
Standard: EN 795-B, CEN/TS/16415

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Temporary Lifeline Horizontal Skylotec L-0329

Technical data

Part code	Min. breaking force kN	Max. number of persons	Length m	Weight kg
8405L0329	6	2	20	2.87

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved