

## Magnetic Steel Former Starcon

### Product information



Starcon steel former are available with and without magnetic accessories to streamline the disassembly process. They are designed in a hemispherical design, where the spherical anchor can be easily placed in the former and then in the concrete element before pouring.

After the mold has been removed, it is easy and safe for the Starcon lifting eye to grab the anchor head and perform a safe lift without the lifting eye encountering the concrete. The former are made of steel and can be used several times, provided they are cleaned and lubricated after each use. Starcon steel formers are offered with and without magnets with a holding force of 50 kN.

**Applications:** The former are used to ensure that the spherical anchor head is not covered by concrete during pouring.

**Advantages:** Quick coupling and disconnection of the spherical anchor.

This product is recyclable.

**Load group:** 1.3t – 10t

**Technical information:** CE marking according to MD 2006/42 EC

**Marking:** Load group + S(Starcon)

**Finish:** Untreated - Corrosion class C1 - ISO 12944-2

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Part code	Load grp. t	D mm	d mm	H mm	M mm	L	Ø mm	h mm	Packing Qty.	Delivery time
650317013001	1 - 1.3	60	20.5	28	8	11	20.5	5	1	10
650317025001	1.5 - 2.5	74	30	33	10	11	20.5	5	1	10
650317050001	3.0 - 5.0	94	38	43	10	15	20.5	5	1	10
650317100001	10	118	48	53	12	15	20.5	5	1	2
650317200001	20	160	71	71	16	20	20.5	5	1	10

## Blueprint

