

Transport Anchor with cross hole Starcon

Product information

STARCON Transport Anchors with cross hole with inside thread for transport and fixing of concrete elements.

The transport anchor with cross hole can be used together with the reinforcement bar which is bent and mounted in the lower cross hole.

Using a transport anchor with cross hole is one of the best ways of lifting and fixing concrete wall elements or tunnel elements.

Transport anchors with cross hole are also available with metric thread.

Material: Steel S355.

Marking: According to standard, Load Group+Starcon, batch code, CE.

Temperature range: 100°C.
Finish: Electro-galvanized (silver).

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contactor Denmark

A/S - Starcon for information on the applicable delivery time.

Subject to prior sale!

Part Code	Dimensions mm	L mm	Ø D mm	e mm	ø g mm	Delivery time
650530NK3012ZN	M12 X 60 MM WITH CROSS HOLE	60	16	24	10	100
650530NK3016ZN	M16 X 79 MM WITH CROSS HOLE	79	21	31	13	2
650530NK3020ZN	M20 X 99 MM WITH CROSS HOLE	99	27	37	15	2
650530NK3024ZN	M24 X 110 MM WITH CROSS HOLE	110	31	40	18	2
650530NK3030ZN	M30 X 156 MM WITH CROSS HOLE	156	39.5	56	20	2

Technical data

Measures - reinforcement mm		
ds	G	D
8	300	60
10	350	70
12	400	80
14	450	100
16	600	130
16	600	130

Blueprint

