

## Transport Anchor with Cross Pin Starcon

### Product information



Starcon transport anchors with cross pin with inside thread for transport and fixing of concrete elements.

The transport anchor with cross pin can be mounted directly to the reinforcement mesh in precast concrete elements. Using a transport anchor with cross pin is one of the best ways of lifting and fixing concrete wall elements or tunnel elements. Transport anchors with cross pin are also available with metric thread.

**Material:** Steel S355.

**Marking:** According to standard, Load Group+Starcon, batch code, CE.

**Temperature range:** 100°C.

**Finish:** Electro-galvanized (silver).

**Standard:** CEN/TR 15728 - VDI/BV-BS 6205

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Subject to prior sale!

Part Code	Dimensions mm	L mm	Ø D mm	e mm	L1 mm	ø g mm	A mm	Delivery time
650535NK3012ZNP	M12 X 60 MM WITH CROSS PIN	60	16	24	60	10	14	100
650535NK3016100ZNP	M16 X 100 MM WITH CROSS PIN	100	21	31	80	12	20	2
650535NK3016ZNP	M16 X 79 MM WITH CROSS PIN	79	21	31	80	12	20	2
650535NK3020120ZNP	M20 X 120 MM WITH CROSS PIN	120	27	37	100	14	24	2
650535NK3020ZNP	M20 X 99 MM WITH CROSS PIN	99	27	37	100	14	24	2
650535NK3024ZNP	M24 X 115MM WITH CROSS PIN	115	31	40	100	14	24	2