

## STA Z 2-hole Anchor Starcon

### Product information



The Starcon STA-Z transport anchor, also known as the two-hole anchor, is designed with two holes, which ensures a strong anchoring in the concrete by using reinforcement in the lower hole. The anchor head contains a hole for attaching a Starcon ring coupling.

This design allows for a high lifting capacity in thin elements, making the STA-Z transport anchor ideal for use in precast concrete elements that require reliable and safe lifting.

**Areas of application:** Lightweight concrete, low concrete compressive strength, wells and thin walls.

**Advantages:** Quick connection/disconnection with moulds and Starcon ring coupling

**Load group:** 1.4t – 26t

**Technical information:** CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

**EPD:** Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

**Download the EPDs from the LCA database:**

Untreated Products: [Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD-Global - Powered by EPD-Norway](#)

Surface treated Products: [Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD-Global - Powered by EPD-Norway](#) ... [Read more](#)


**Marking:** CE-marked, batch code, load group + S(Starcon)

**Finish:** Untreated - Corrosion class C1 - ISO 12944-2. Hot-dip galvanized - Corrosion class C3 - ISO 12944-2

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) to get information about the applicable delivery time.

## STA Z 2-hole Anchor Starcon

### Blueprint



### Technical data

Part code	Load grp. t	Length mm	Finish	L mm	a mm	b mm mm	c mm	Hole mm mm	Weight kg	Packing Qty.
65012602500901	2.5	90	Untreated	90	30	14	10	14x20	0.16	150
65012602500902	2.5	90	Hot dip galvanized	90	30	14	10	14x20	0.17	150
65012605001201	5	120	Untreated	120	40	20	15	20x22	0.42	35
65012605001202	5	120	Hot dip galvanized	120	40	20	15	20x22	0.42	35
65012607501601	7.5	160	Untreated	160	60	26	16	26x30	0.91	16
65012607501602	7.5	160	Hot dip galvanized	160	60	26	16	26x30	0.92	16
65012610001701	10	170	Untreated	170	60	28	20	28x30	1.26	12
65012610001702	10	170	Hot dip galvanized	170	60	28	20	28x30	1.26	12
65012614002401	14	240	Untreated	240	80	35	20	35x46	2.36	5
65012614002402	14	240	Hot dip galvanized	240	80	35	20	35x46	2.36	5
65012622003001	22	300	Untreated	300	90	35	28	35x46	4.74	1
65012622003002	22	300	Hot dip galvanized	300	90	35	28	35x46	4.74	1
65012626003001	26	300	Untreated	300	120	65	30	35x45	6.2	1
65012626003002	26	300	Hot dip galvanized	300	120	65	30	35x45	6.25	1