



STA-SA Universal and Erection Anchor Conical

Product information

The Transport Anchor STA-SA - CONIC is suitable for loads from 0.7 up to 22.0 t. The conical transport anchor is designed for the tipping of panels from a horizontal to a vertical position. The conical anchor is used for erection and turning of precasted thin wall units in both directions. The head of the anchor has a hole in which the locking bolt of the lifting eye is mounted. Other holes in the anchor are meant for further reinforcement. The head of the anchor is designed so that the load cannot be transferred to the upper part of the concrete surface.

Surface: Black or hot dip galvanized.

Material: Steel S355.

Marking: According to standard, CE-marked, Load group + Starcon, batch code

Temperature range: 200°C

Standard: CEN/TR 15728 - VDI/BV-BS 6205

Note: The delivery time for the individual products is estimated. If the desired quantity is not in stock, please contact [CERTEX Danmark A/S](#) – [Starcon](#) for information on the applicable delivery time.

Part Code	WLL ton	b mm	c mm	d mm	l mm	Weight kg	Delivery time
6501TPASA0142000	1.4	50	6	15	200	0.38	100
65012402502301	2.5	50	10	15	230	0.674	2
65012305002901	5	70	15	20	290	1.894	2
65012312505001	12.5	150	20	35	500	6.438	100
65012317005001	17	150	25	35	500	6.82	100
65012322005001	22	150	30	36	500	9.96	100

Blueprint

