



# STA-SE One-sided Anchor Starcon

## Product information

The Starcon STA-SE is designed specifically to tilt panels from horizontal to vertical position in the direction where the notch is located. Unlike the STA-SA anchor, the STA-SE anchor can only handle loads in one direction, making it particularly suitable for thin elements or elements with limited space for the anchor location.

The anchor head has a hole for mounting the ring coupling locking bolt and additional holes for reinforcement located in the center of the anchor. This makes the STA-SE anchor ideal for tilting and turning prefabricated elements, as well as for erecting and mounting.

**Areas of application:** Concrete elements that need to be turned

**Advantages:** Multiple reinforcement placement options to ensure optimal lifting performance.

Flipping Elements

Quick connection/disconnection with shapes and Starcon ring coupling, perfect for efficient transport and setup.

**Load group:** 2.5t – 17t

**Technical information:** CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

**EPD:** Our Environmental Product Declarations (EPDs) are available in the LCA NO calculator/software. These EPDs have been prepared in strict accordance with ISO 14025 and EN 15804 standards.

**Download the EPDs from the LCA database:**

Untreated Products: [Starcon Lifting and Handling Systems for Concrete elements - Untreated - EPD Norge](#)

Surface treated Products: [Starcon Lifting and Handling Systems for Concrete elements - Surface Treated. - EPD Norge](#)

**Marking:** CE-marked, batch code, load group + S(Starcon)

**Finish:** Untreated - Corrosion class C1 - ISO 12944-2. Hot-dip galvanized - Corrosion class C3 - ISO 12944-2

**Note:** The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

Part code	Load grp. t	Length mm	Finish	c mm	L mm	a mm	g mm	r mm	Hole mm	Weight kg	Packing Qty.	Delivery time
65012402502301	2.5	230	Untreated	10	230	40	45	7	14x20	0.63	100	2
65012405002901	5	290	Untreated	15	290	55	70	10	20x22	1.64	30	2
65012407503201	7.5	320	Untreated	15	320	80	90	13	26x30	2.65	17	2
65012410003901	10	390	Untreated	20	390	80	90	15	26x30	4.42	12	2

## Blueprint

