



Ring Clutch Starcon

Product information

The Starcon ring clutch is a specially designed component with a bolt-shaped ring that grips the hole of the Starcon STA anchor. It enables quick and secure mounting of the ring coupling to the STA anchors by means of a locking bolt that mechanically locks to the anchor.

The ring coupling can be easily connected to a sling or hook, making lifting both fast and safe. It is ideal for use with lifting equipment and cranes, ensuring efficient and reliable handling of concrete elements.

Areas of application: The Starcon ring clutch is used for lifting Starcon STA anchors

Advantages: Ensures handling of concrete elements.

Enables safe lifting in all directions.

Quick and easy installation.

Load group: 2.5t – 10t

Technical information: CE marking according to MD 2006/42 EF

Starcon product is designed according to EN13155-2009 and follows the guidelines of VDI/BV-BS 6205 and DS/CEN/TR 15728.

Marking: CE-marked, batch code, load group + S(Starcon)

Finish: Electro-galvanized - Corrosion class C3 - ISO 12944-2.

Note: The delivery time for the individual products is estimated and if the desired quantity is not in stock, please contact [CERTEX Danmark A/S – Starcon](#) for information on the applicable delivery time.

| Part code | Load grp. t | a mm | b mm | c mm | d mm | t mm | L mm | Weight kg | Packing Qty. | Delivery time |
|--------------|-------------|---------|---------|---------|---------|---------|---------|--------------|--------------|---------------|
| 650290025001 | 2.5 | 70 | 54 | 79 | 27 | 12.5 | 223 | 0.95 | 1 | 2 |
| 650290050001 | 5 | 85 | 59.5 | 107 | 37 | 17 | 281 | 1.5 | 1 | 2 |
| 650290100001 | 10 | 110 | 82.5 | 148 | 50 | 25 | 352 | 3.18 | 1 | 2 |

Blueprint

