

Push Trolley type 20

Product information



Low-built block trolley for hanging e.g. chain blocks and wire hoists. The trolley can be supplied with a load of 0.5 tons up to 10 tons. The trolley has corner protection which prevents the trolley from detaching from the beam and ball bearing wheels. It is easily adjustable by the left- and right-handed carrier bracket and fits most brands of hoists.

Marking: CE-marked, WLL, name plate and beam width

Temperature range: -10°C up to +50°C

Finish: Powdercoated steel sides

Part code	WLL ton	Beam width mm	Model	Minimum radius mm	A mm	B mm	C mm	D, mm	E mm	F mm	G, mm	H, mm	J mm	K mm	L mm	Mmm mm	Pmm mm	Weight kg	Delivery time
502300051600420	0.5	46-160	20123A	1,000	46-160	208	18	62	77	18	45	33	25	19	216	100	24	6	2
502300052800420	0.5	161-280	20124A	1,000	161-280	208	18	62	77	18	45	33	25	19	216	100	24	6.4	10
502300081600420	0.8	46-160	20133A	1,000	46-160	208	18	62	77	18	45	33	25	19	216	100	24	6	10
502300101610420	1	50-160	20143A	1,250	50-160	212	20	70	85	20	51	40	32	24	264	130	26	9.4	10
502300102800420	1	161-280	20144A	1,250	161-280	212	20	70	85	20	51	40	32	24	264	130	26	10.7	10
502300161600420	1.6	50-160	20153A	1,250	50-160	212	20	70	85	20	51	40	32	24	264	130	26	9.4	10
502300201800420	2	64-180	20163A	1,800	64-180	248	24	100	118	24	63	51	40	32	345	165	30	19	10
502300203000420	2	181-300	20164A	1,800	181-300	248	24	100	118	24	63	51	40	32	345	165	30	21	10
502300301800420	3	74-180	20173A	2,200	74-180	262	28	114	137	28	78	57	46	35	384	180	35	31.5	10
502300303000420	3	181-300	20174A	2,200	181-300	262	28	114	137	28	78	57	46	35	384	180	35	34	10
502300321800420	3.2	74-180	20175A	2,200	74-180	262	28	114	137	28	78	57	46	35	384	180	35	19	10
502300501800420	5	82-180	20193A	2,500	82-180	270	34	140	165	34	92	64	56	42	455	215	40	55	10
502300503000420	5	181-300	20194A	2,500	181-300	270	34	140	165	34	92	64	56	42	455	215	40	58	10
502300631800420	6.3	82-180	20203A	2,500	82-180	270	34	140	165	34	92	64	56	42	455	215	40	31.5	10
502300633000420	6.3	181-300	20204A	2,500	181-300	270	34	140	165	34	92	64	56	42	455	215	40	58	10
502300701800420	7	82-180	20213A	2,500	82-180	270	34	140	165	34	92	64	56	42	455	215	40	55	10
502300702400420	7	181-300	20214A	2,500	181-300	270	34	140	165	34	92	64	56	42	455	215	40	58	10
502301003000420	10	220-300	20234	2,500	220-300	98-138	140	495	32	466	215	50	-	-	-	-	-	95	10

Blueprint

