

Trolley type 26

Product information



This geared trolley with manually operated hoist with load pressure break has an extremely low headroom design. The trolleys are available for loads from 1t up to 6.3 t.

Operating height of 3m.

[... Read more](#)

Marking: According to standard, WLL, code and CE marking.


Temperature range: -20°C up to +50°C.

Finish: Painted.

Standard: EN 13157

Trolley type 26

Blueprint



Technical data

Part code	WLL ton	Beam width mm	Model	A mm	B1 mm	B2 mm	C1 mm	C2 mm	D1 mm	D2 mm	E2 mm	E1 mm	F mm	H min mm	L mm	M2 mm	M mm	M1 mm	Weight kg
502600101500080	1	74-150	2614	554	206	234	129	151	117	223	134	217	27,5	135	348	18	28	40	69
502600201560080	2	82-156	2616	684	254	406	149	149	165	265	152	240	36,5	160	392	24	36	50	118
502600322230080	3.2	103-223	2617	765	279	461	169	236	165	325	173	240	44	190	499	28	40	55	181
502600502150080	5	119-215	2619	873	336	524	201	279	184	327	180	259	39	235	512	37	45	65	293
502600632150080	6.3	119-215	2620	873	336	524	201	179	184	327	180	259	39	235	512	37	45	65	296

Art No	WLL	Type	Chain falls	Flange width	Min. curve radius	Load chain	Hand chain Ø	Weight
	tons			mm	mm	mm	mm	kg
16.052614	1	2614	2	74-150	2500	5 x 15	5,0 x 23,7	69
16.052616	2	2616	2	82-156	4000	6,3 x 19,1	5,0 x 23,7	118
16.052617	3,2	2617	2	103-223	4500	8 x 24	5,0 x 23,7	181
16.052619	5	2619	4	119-215	6000	8 x 24	5,0 x 23,7	293
16.052620	6,3	2620	4	119-215	6000	8 x 24	5,0 x 23,7	296