Lifting Solutions Group
Axel Johnson International

Fishing Dee Shackle FP Green Pin® G-4159

Product information



The Green Pin® Fishing Dee Shackle FP is a dee shackle with a square sunken hole screw pin (flush pin). The Green Pin® Fishing Dee Shackle FP contains no protruding parts so it does not damage or get caught in fishing nets. Another important feature is that the chamber in the shackle eye hides the screw thread and reduces wear of rope. Galvanization of the bow shackle ensures its long-term durability. The Green Pin® Fishing Dee Shackle FP is suitable for one-leg lifting systems only and can be assembled with the help of the Green Pin® Sunken Hole Key. The shackle is available in a range with a working load limit from 2 up to 17 ton.

Certification on request: 2.1, 2.2, 3.1, MTCa

... *Read more*

Material: Bow and pin high tensile steel, quenched and tempered
Marking: According to standard, CE-mark
Finish: Hot dipped galvanized
Standard: EN 13889
Note: Key for unscrewing the pin sold separately

Safety factor: 6:1
Grade: 6


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fishing Dee Shackle FP Green Pin® G-4159

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	Weight kg
420100200990	2	13.5	16	34	13	22	43	81	51	11	0.34
420100330990	3.25	16	19	40	16	27	51	97	63	11	0.6
420100480990	4.75	19	22	46	19	31	59	112	74	11	0.98
420100650990	6.5	22	25	52	22	36	73	134	85	13	1.26
420100850990	8.5	25	28	59	25	43	85	154	99	13	2.14
420100950990	9.5	28	32	66	28	47	90	167	110	17	3.05
420101700990	17	38	42	88	38	60	127	230	145	17	6.84

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved