

## Snatch Block Green Pin® type 601H P-6952

---

### Product information



The Green Pin® Snatch Block HK is a light-weight snatch block type 601HK with a hook attached. The snatch block has a smooth, uninterrupted pull due to the conical roller bearings. The coating of the Green Pin® Snatch Block HK ensures long-term durability, even under harsh conditions. It is available in a range with a working load limit from 2 up to 15 ton.

Certification on request: 2.1, 2.2, MTCb

... [Read more](#)

---

**Material:** Carbon steel, fitted with conical roller bearings

**Marking:** CE-marked


**Finish:** Painted

**Note:** WLL is on the headfitting

**Safety factor:** 4:1

## Snatch Block Green Pin® type 601H P-6952

Blueprint



## Snatch Block Green Pin® type 601H P-6952

### Technical data

Part code	Rope Ø range mm	WLL ton	Sheave dia mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	Weight kg
4241BKOFFSH0302	7-9	2	75	75	290	87	82	28	108	3.68
4241BKOFFSH0404	10-12	4	115	115	358	89	120	43	125	6
4241BKOFFSH0804	10-12	4	200	200	473	91	210	40	125	8
4241BKOFFSH0604	12-14	4	150	150	412	89	160	40	125	8.5
4241BKOFFSH0608	20-22	8	150	150	502	119	160	48	165	11.8
4241BKOFFSH0808	20-22	8	200	200	551	119	210	48	165	20.4
4241BKOFFSH1008	20-22	8	250	250	606	103	260	46	165	25.4
4241BKOFFSH1208	20-22	8	300	300	671	119	310	46	165	32
4241BKOFFSH1408	20-22	8	350	350	716	119	360	46	165	38
4241BKOFFSH1608	20-22	8	400	400	780	119	415	46	165	48
4241BKOFFSH1808	20-22	8	450	450	841	119	465	46	165	58
4241BKOFFSH0612	20-22	12	152	150	616	119	160	70	236	20.5
4241BKOFFSH0812	20-22	12	200	200	641	129	210	70	236	30
4241BKOFFSH1012	20-22	12	250	250	728	125	260	70	236	35.5
4241BKOFFSH1612	20-22	12	400	400	888	166	415	70	236	36
4241BKOFFSH1812	20-22	12	450	450	942	166	465	70	236	42
4241BKOFFSH1212	20-22	12	300	300	810	166	310	70	236	50
4241BKOFFSH1412	20-22	12	350	350	835	166	360	70	236	59
4241BKOFFSH0615	24-26	15	150	150	626	138	160	70	236	23.5
4241BKOFFSH0815	24-26	15	200	200	663	142	210	70	236	29.5
4241BKOFFSH1015	24-26	15	250	250	745	166	260	70	236	41
4241BKOFFSH1215	24-26	15	300	300	810	166	310	70	236	52
4241BKOFFSH1415	24-26	15	350	350	837	166	360	70	236	58.5
4241BKOFFSH1615	24-26	15	400	400	890	166	415	70	236	68.5
4241BKOFFSH1815	24-26	15	450	450	942	166	465	70	236	82