



Clevis Grab Hook Green Pin® CRC

Product information

Grab hooks are designed with a special curved narrow throat used to "grab" and shorten or hold a length of chain used in general lifting applications.

In case of asymmetric load, the grab hook can be used to adjust one or more legs of the sling. The curved design of this throat makes inserting the chain easier and quicker. Once fitted the chain is perfectly secured, because the curved throat avoids the chain to slip out and two pitches support the link properly. The clevis design enables a direct connection to grade 8 chain. When connecting the clevis hook to a master link, use at least 3 grade 8 chain links between the hook and the connecting link fixed on the master link. 100% load capacity.

Certification: 2.1 2.2 3.1 MPI b.

Material: Alloy steel, quenched and tempered.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted yellow (J), red (R) or white

Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

| Part code | Chain diameter mm | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | Weight kg | Delivery time |
|--------------|----------------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 401300110420 | 6 | 1.12 | 52 | 7 | 28 | 7 | 24 | 19 | 42 | 86 | 8 | 0.28 | 10 |
| 401300200420 | 7-8 | 2 | 64 | 9 | 32 | 10 | 33 | 23 | 53 | 104 | 9 | 0.45 | 10 |
| 401300320420 | 10 | 3.2 | 75 | 12 | 42 | 12 | 40 | 29 | 66 | 127 | 13 | 0.88 | 10 |
| 401300540420 | 13 | 5.4 | 103 | 15 | 54 | 15 | 56 | 40 | 88 | 173 | 16 | 2.17 | 10 |
| 401300820420 | 16 | 8.2 | 127 | 19 | 68 | 18 | 65 | 43 | 96 | 208 | 20 | 2.81 | 10 |

Blueprint

