

Clevis Sling Hook Green Pin® CSC



Product information

The sling hook can be used for general lifting applications. It can be quickly connected to the load lifting points thanks to its easy operating latch, which guarantees full safety. To connect simply push the latch, connect the hook to the lifting point, and release the latch. The forged latch guarantees a longer lifespan. It strongly limits the risk that the operator uses the hook without latch. The latch is fitted with a stainless steel spring and a sturdy pin. The clevis design enables a direct connection to grade 8 chain. The Green Pin® Sling Hook CL is available in a range to suit 5 mm up to 22 mm grade 8 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

Material: Alloy steel, quenched and tempered.

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted white

Standard: EN 1677-2

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Weight kg	Delivery time
401300110460	6	1.12	76	7	27	15	19	28	73	108	8	0.29	10
401300200460	7-8	2	95	9	30	20	22	32	85	133	9	0.58	10
401300320460	10	3.2	113	11	33	24	28	42	106	164	13	1.1	2
401300540460	13	5.4	138	15	35	32	40	54	133	208	16	2.12	2
401300820460	16	8.2	161	18	43	40	44	67	165	240	20	3.67	10
401301280460	18-20	12.8	233	22	62	49	65	82	236	342	24	7.32	10
401301550460	22	15.5	235	24	77	54	60	96	227	343	28	10.63	10

Blueprint

