



Eye Grab Hook Green Pin® CRO

Product information

The Green Pin® Grab Hook E is a grade 8 eye grab hook according to European standard for components for sling EN 1677-1. Grab hooks are designed with a special curved narrow throat used to "grab" and shorten or hold a length of chain used in general lifting applications. In case of asymmetric load, the grab hook can be used to adjust one or more legs of the sling. The curved design of this throat makes inserting the chain easier and quicker. Once fitted the chain is perfectly secured, because the curved throat avoids the chain to slip out and two pitches support the link properly. The flat on the eye enables the assembly with an omega link. 100% load capacity. For a safe connection to a master link, check the 'frequently asked questions' below. The Green Pin® Grab Hook E EN1677-1 is available in a range to suit 6 mm up to 32 mm grade 8 chain.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb, DGUV

Material: Alloy steel, quenched and tempered

Marking: According to standard

Temperature range: -40°C up to +200°C

Finish: Painted white

Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	a mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	Weight kg	Delivery time
401300110400	6	1.12	41	24	23	8	24	20	42	94	9	6	0.25	10
401300200400	7-8	2	53	27	26	10	33	23	53	115	10	8	0.45	2
401300320400	10	3.2	65	38	36	12	40	29	66	146	14	10	0.91	2
401300540400	13	5.4	83	42	41	15	56	40	88	183	16	12	1.99	10
401300820400	16	8.2	103	44	41	18	66	43	96	211	20	20	2.49	2
401301280400	20	12.8	130	37	37	22	75	48	128	241	26	26	4.3	2
401301550400	22	15.5	120	44	44	25	77	57	132	247	26	26	8.5	10
401302160400	26	21.6	158	46	46	30	100	82	177	320	32	32	14.7	2
401303280400	32	32.8	210	57	57	38	91	88	215	395	39	39	18	10

Blueprint

