Cam Buckle Mini POWERTEX

Product information



Cam buckle Mini web lashings. Available in different colours and lengths from 0,6 – 5,0 m. Webbing width is 25 or 35 mm.

Suitable for fast lashing and for keeping items together.

... *Read more*

Material: Polyester webbing and zink casted cambuckle
Marking: According to standard, POWERTEX, LC, length, manufacturing year, batch number, serial number, inspection calendar
Temperature range: -40°C up to +120°C
Standard: EN 12195-2
Note: Protect the lashings from sharp edges

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Cam Buckle Mini POWERTEX

Technical data

Part code	LC daN	2xLC (daN)	Length m	Width mm	Band width mm	Design	Colour	Weight kg
700100061000014	125	250	0.6	25	25	Endless	Black	0.06
700100101000014	125	250	1	25	25	Endless	Black	0.068
700100101000012	125	250	1	25	25	Endless	Red	0.068
700100151000012	125	250	1.5	25	25	Endless	Red	0.078
700100201000014	125	250	2	25	25	Endless	Black	0.088
700100201000019	125	250	2	25	25	Endless	Orange	0.088
700100301000015	125	250	3	25	25	Endless	Blue	0.108
700100401000013	125	250	4	25	25	Endless	Green	0.128
700100501000014	125	250	5	25	25	Endless	Black	0.148
700100501000012	125	250	5	25	25	Endless	Red	0.148
700300101000014	300	600	1	35	35	Endless	Black	0.185

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© October 2026 - All Rights Reserved