Lifting Arm NEO HV

Product information



The Neo HV lifting arm, in connection with a Neo lifting magnet, is a versatile aid for handling loads from the horizontal to the vertical position and vice versa. For example, if a plate is on a pallet and you need to move it to a lathe, you must usually make use chains, clamps, and at least two workers. With a lifting arm equipped with a Neo permanent lifting magnet, you will save manpower and make the operation more efficient.

Features:

- Possibility to adjust the arm to a wide range of diameters and widths
- Removable lifting arm for magnet replacement
- Robust lifting eye

... *Read more*

Marking: According to standard
Temperature range: Up to +80°C
Finish: Painted.
Standard: EN 13155
Note: Only suitable for NEO and NEO HOT, which have to be ordered separately.

Safety factor: 3:1


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Arm NEO HV

Blueprint



Technical data

Part code	Code	WLL ton	Width mm	W mm	L mm	H mm	Weight kg
503100030000150	LARM250	0.25	300-800	210	958	244	16
503100050000150	LARM500	0.5	300-1,000	210	1,158	244	20
503100100000150	LARM1000	1	300-1,000	210	1,211	297	33

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved