



Lifting Arm NEO HV

Product information

The Neo HV lifting arm, in connection with a Neo lifting magnet, is a versatile aid for handling loads from the horizontal to the vertical position and vice versa. For example, if a plate is on a pallet and you need to move it to a lathe, you must usually make use of chains, clamps, and at least two workers. With a lifting arm equipped with a Neo permanent lifting magnet, you will save manpower and make the operation more efficient.

Features:

- Possibility to adjust the arm to a wide range of diameters and widths
- Removable lifting arm for magnet replacement
- Robust lifting eye

Marking: According to standard

Temperature range: Up to +80°C

Finish: Painted.

Standard: EN 13155

Note: Only suitable for NEO and NEO HOT, which have to be ordered separately.

Safety factor: 3:1

| Part code | Code | WLL ton | Width mm | W mm | L mm | H mm | Weight kg | Delivery time |
|-----------------|----------|------------|-------------|---------|---------|------|--------------|---------------|
| 503100030000150 | LARM250 | 0.25 | 300-800 | 210 | 958 | 244 | 16 | 10 |
| 503100050000150 | LARM500 | 0.5 | 300-1,000 | 210 | 1,158 | 244 | 20 | 10 |
| 503100100000150 | LARM1000 | 1 | 300-1,000 | 210 | 1,211 | 297 | 33 | 10 |

Blueprint

