

## **Anchorage Point PSA-YEP**

## **Product information**



- Rotates through 360° adjustable in the direction of the load.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Passed 150 kg dynamic fall testing (EU standard is 100 kg).
- Meets all requirements of the German BG BAU ( Employer s insurance association of the building industry).
- Correspond to the European Directive for "personnel protection equipment" (89/686/EWG).
- PSA Lifting point to be as an anchor point for personal protective equipment.

Features: Built-in RFID/NFC chip

Material: Manufactured from forged alloy steel, quenched and tempered

Marking: According to standard, number of persons, standards, individual serial number, manufacturer, production year, product ID

Finish: Yellow Painted

**Standard:** EN 795, EN 365, EN 50308

| Part code   | Max. number of persons | Torque<br>Nm | A mm | B mm | C mm | D<br>mm | E<br>mm | F<br>mm | G<br>mm | H<br>mm | J<br>mm | S<br>mm | W<br>mm | M<br>mm    | Weight<br>kg | Delivery time |
|-------------|------------------------|--------------|------|------|------|---------|---------|---------|---------|---------|---------|---------|---------|------------|--------------|---------------|
| 84158281007 | 1                      | 10           | 45   | 30   | 10   | 11      | 18      | 33      | 29      | 5       | 45      | 8       | 52      | M12 x 1.75 | 0.2          | 2             |
| 84158281015 | 2                      | 30           | 52   | 35   | 14   | 13      | 24      | 35      | 33      | 8       | 52      | 10      | 61      | M16 x 2    | 0.3          | 10            |
| 84158281023 | 2                      | 70           | 60   | 40   | 16   | 15      | 30      | 44      | 37      | 7       | 60      | 12      | 70      | M20 x 2.5  | 0.6          | 2             |

## Blueprint

