

## Clevis Foundry Hook X-046 Grade 10

---

### Product information



At least 25% greater WLL than traditional Grade 8 products.  
Testing according to DIN PAS 1061 and ASTM A952/A 952M.  
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.  
Tempering temperature minimum 400°C.  
Designed for the assembly of chain slings where wide throat openings are necessary.

... [Read more](#)

---

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1


**Warning:** Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

**Safety factor:** 4:1

**Grade:** 10

## Clevis Foundry Hook X-046 Grade 10

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	H, mm	K mm	Pmm mm	T mm	Weight kg
402300250770	7-8	2.5	133	9	27	133	62	19	0.95
402300400770	10	4	163	11	32	163	74	23	1.8
402300670770	13	6.7	200	14	39	200	88	32	3.6