Lifting Solutions Group
Axel Johnson International

Eye Foundry Hook X-047

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Designed for the assembly of chain slings where wide throat openings are necessary

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL

... Read more

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Size, grade, manufacturer ID, traceability.
Temperature range: -40ºC up to +200°C (without reduction in WLL).
Standard: EN 1677-1
Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1
Grade: 10


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Eye Foundry Hook X-047

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg
402300250800	7-8	2.5	123	24	12	30	123	62	19	0.8
402300400800	10	4	149	32	15	35	149	74	23	1.6
402300670800	13	6.7	180	40	19	39	180	88	32	2.6
402301000800	16	10	213	50	25	46	213	98	41	4.5
402301600800	20	16	248	60	26	59	248	113	58	9.3

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37
© November 2026 - All Rights Reserved