

Eye Grab Hook X-041

Product information



At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Painted.

Standard: EN 1677-1

Note: Not for use with Omega Link

Safety factor: 4:1

Grade: 10

Part code	WLL ton	A mm	B mm	F mm	G mm	K mm	P mm	Weight kg	Delivery time
402300140740	1.4	13	7	26	8	50	8	0.2	2
402300250740	2.5	16	10	30	9	62	10	0.3	2
402300400740	4	20	13	40	13	82	13	0.6	2
402300670740	6.7	26	16	52	16	107	17	1.4	2
402301000740	10	30	18	70	20	132	21	2.4	2
402301600740	16	40	22	73	24	148	24	4	2
402301900740	19	42	24	86	26	166	26	5	2
402302650740	26.5	50	30	110	32	207	33	10.1	10

Blueprint

