



Eye self-locking Hook X-025

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part code	WLL ton	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
402300140720	1.4	21	10	19	110	28	15	0.5	2
402300250720	2.5	25	11	24	136	34	20	0.8	2
402300400720	4	32	13	30	167	44	26	1.5	2
402300670720	6.7	40	16	39	207	51	30	3	2
402301000720	10	50	21	49	252	60	36	5.8	2
402301600720	16	60	23	65	290	70	53	10	2
402301900720	19	70	24	63	319	80	49	12.5	2
402302650720	26.5	80	25	69	343	99	56	15	2

Blueprint

