



Connecting Link X-015 Grade 10

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	K mm	Weight kg	Delivery time
402200140190	6	1.4	45	15	17	7	45	0.08	2
402200250190	7-8	2.5	59	18	23	9	59	0.2	10
402200400190	10	4	69	25	27	11	69	0.3	2
402200670190	13	6.7	92	30	37	16	92	0.7	2
402201000190	16	10	101	36	39	19	101	1.2	2
402201600190	20	16	122	42	46	23	122	2.1	2
402201900190	22	19	152	49	59	24	152	3.5	2
402202650190	26	26.5	162	55	62	30	162	4.8	2
402204000190	32	40	203	69	79	36	203	9	2

Blueprint

