



Master Link Grab 1 Assy X-A04, Yoke

Product information

- Fully integrated shortening hook and master link.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- No reduction in WLL when shortening chain.
- Speedy assembly.
- Light weight system.
- Cost effective compared to slings which use multiple components.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	EWL mm	DIN 15401 Hook No.	D mm	A mm	B mm	K mm	Weight kg	Delivery time
402100140460	6	1.4	120	4	13	120	70	196	0.7	2
402100250460	8	2.5	140	5	16	140	80	242	1.2	10
402100400460	10	4	160	6	19	160	95	285	2.1	2
402100670460	13	6.7	170	10	22	170	105	328	3.9	2
402101000460	16	10	190	10	28	190	110	392	7	10

Blueprint

