



Master Link Grab 1 Assy X-A06

Product information

At least 25% greater WLL than traditional Grade 8 products.
 Fatigue rated to 20,000 cycles at 1.5 times the WLL.
 Fully integrated shortening hooks and master link.
 No reduction in WLL when shortening chain.
 Speedy assembly.
 Light weight system.
 Cost effective compared to slings which use multiple components.
 Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Chain diameter mm	WLL ton	WLL 45- 60° ton	WLL 0-45° ton	D mm	A	B mm	K mm	Weight kg	Delivery time
402100290480	6	2.9	2,1	2,9	19	160	95	290	2.4	10
402100530480	8	5.3	3,8	5,3	22	170	105	342	4.6	10
402100840480	10	8.4	6,0	8,4	28	190	110	400	8.1	2
402101410480	13	14.1	10,1	14,1	32	230	130	503	15.8	10
402102100480	16	21	15,0	21,0	36	275	150	617	28.9	10

Blueprint

