



Welded Master Link Assembly X-006L

Product information

Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.

At least 25% greater WLL than traditional Grade 8 products. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	Proof Load kN	Used to single hook acc. to DIN 15401 No.	A mm mm	B mm mm	D mm	a mm	b mm	d mm	Weight kg	Delivery time
402100420450	BD-19 + 2 DD+13	4.2	103	5	135	75	19	110	60	13	1.6	10
402100820450	BD-22 + 2 DD+16	8.2	201	6	160	90	22	110	60	16	2.5	2
402101070450	BD-32 + 2 DD+22	10.7	262	10	200	110	32	160	90	22	6.9	2
402101570450	BD-36 + 2 DD+28	15.7	385	16	260	140	36	180	100	28	11.8	2
402102220450	BD-45 + 2 DD+32	22.2	544	25	300	180	45	200	110	32	19.7	2

Blueprint

