



Welded Master Link X-002

Product information

Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings. The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Tempering temperature at a minimum of 400°C.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | EWL mm | For chain, 1-leg mm | For chain, 2-leg mm | A mm | B mm | D mm | Weight kg | Delivery time |
|--------------|-------|---------|--------|---------------------|---------------------|------|------|------|-----------|---------------|
| 402100280420 | BD-13 | 2.8 | 110 | 7,8 | 6 | 110 | 60 | 13 | 0.3 | 2 |
| 402100400420 | BD-16 | 4 | 110 | 10 | 7,8 | 110 | 60 | 16 | 0.5 | 2 |
| 402100670420 | BD-19 | 6.7 | 135 | 13 | 10 | 135 | 75 | 19 | 0.9 | 10 |
| 402100850420 | BD-22 | 8.5 | 160 | 13 | 10 | 160 | 90 | 22 | 1.5 | 2 |
| 402101150420 | BD-28 | 11.5 | 180 | 16 | 13 | 180 | 100 | 28 | 2.7 | 2 |
| 402101700420 | BD-32 | 17 | 200 | 20 | 16 | 200 | 110 | 32 | 3.9 | 10 |
| 402102510420 | BD-36 | 25.1 | 260 | 22 | 20 | 260 | 140 | 36 | 6.3 | 2 |
| 402103830420 | BD-45 | 38.3 | 300 | 26 | 22 | 300 | 180 | 45 | 11.8 | 10 |
| 402104500420 | BD-50 | 45 | 300 | 32 | 26 | 300 | 200 | 50 | 15.2 | 2 |

Blueprint

