Lifting Solutions Group
Axel Johnson International

# Clevis Grab Hook X-042

**Product information**



- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... *Read more*

**Material:** Quenched and Tempered Alloy Steel
**Marking:** According to standard, Size, grade, manufacturer ID, traceability.
**Temperature range:** -40ºC up to +200°C (without reduction in WLL).
**Standard:** EN 1677-1
**Warning:** Not for use with Omega Link

**Safety factor:** 4:1
**Grade:** 10

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Clevis Grab Hook X-042

## Blueprint




## Technical data

| Part code | Chain diameter mm | WLL ton | EWL mm | A mm | F mm | H mm | K mm | L mm | P mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|
| 402300140810 | 6 | 1.4 | 47 | 7 | 25 | 18 | 47 | 79 | 8 | 0.2 |
| 402300250810 | 7-8 | 2.5 | 54 | 10 | 30 | 22 | 54 | 93 | 10 | 0.4 |
| 402300400810 | 10 | 4 | 77 | 11 | 41 | 29 | 77 | 128 | 13 | 0.8 |
| 402300670810 | 13 | 6.7 | 99 | 15 | 52 | 38 | 99 | 165 | 17 | 1.6 |
| 402301000810 | 16 | 10 | 114 | 18 | 57 | 45 | 114 | 195 | 21 | 2.7 |
| 402301600810 | 20 | 16 | 130 | 22 | 73 | 52 | 130 | 222 | 23 | 4.8 |
| 402301900810 | 22 | 19 | 139 | 24 | 70 | 56 | 139 | 247 | 26 | 6.4 |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved