



## Connecting Link Green Pin Tycan® UMJT

### Product information

The Green Pin Tycan® Connecting Link GR10 is used for connecting Green Pin Tycan® chain slings. The Connecting Link is made from grade 10, high tensile steel and is available in a range with a working load limit from 2.6 ton up to 10.3 ton and a lashing capacity of 10 and 13.6 ton. Spare bushes for the connecting link are also available separately.

Certification on request: 2.1, 2.2, 3.1, MTCa, MPIb

**Material:** Alloy steel

**Marking:** According to standard, Manufacturer ID, chain diameter, traceability code, steel grade, item code and origin

**Temperature range:** -40°C up to +200°C

**Finish:** Blue painted

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part code	WLL ton	LC kN	For chain Ø mm	a mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	Weight kg	Delivery time
402200260220	2.6	54	11x15	9	57	14	20	55	16	19	13	0.22	2
402200400220	4	80	11x20	12	66	18	23	64	18	23	16	0.37	10
402200680220	6.8	136	13x30	16	83	21	32	85	24	28	20	0.78	10

# Blueprint

