



## Swivel self-locking Hook X-027N

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Rotate when loaded.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Built with ball bearing and enables full swivel feature under load.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C .

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

Part code	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
420500140950	1.4	32	23	12	19	149	28	15	0.7	2
420500250950	2.5	36	29	13	24	186	34	20	1.2	2
420500400950	4	41	35	16	30	218	44	26	2	2
420500670950	6.7	46	44	21	39	276	51	30	4.1	10
420501000950	10	61	50	23	49	329	60	36	7.2	2
420501600950	16	74	82	25	65	403	70	53	13	2
420501900950	19	97	96	33	63	454	80	49	20	10
420502650950	26.5	123	116	51	69	535	99	56	33	10

## Blueprint

