

Long Link Chain DIN 763 - Hot-dip galvanized

Product information

Long-link chain for luminaire suspension, exhibition purposes, etc. Delivered hot-dip galvanized as standard.


... [Read more](#)

Marking: According to standard

Finish: Hot dip galvanized


Standard: DIN 763, DIN 5685C

Warning: Not approved for lifting



Long Link Chain DIN 763 - Hot-dip galvanized

Blueprint



Technical data

| Part code | Chain diameter mm | MBL ton | B mm | C mm | D mm | Weight kg/m |
|-----------------|-------------------|---------|------|------|------|-------------|
| 200500300000040 | 3 | 0.28 | 12 | 26 | 3 | 0.15 |
| 200500400000040 | 4 | 0.6 | 16 | 32 | 4 | 0.27 |
| 200500500000040 | 5 | 1 | 20 | 35 | 5 | 0.43 |
| 200500600000040 | 6 | 1.4 | 24 | 42 | 6 | 0.64 |
| 200500800000040 | 8 | 2.5 | 32 | 52 | 8 | 1.15 |
| 200501000000040 | 10 | 4 | 40 | 65 | 10 | 1.75 |
| 200501400000040 | 13 | 6.4 | 50 | 82 | 13 | 2.93 |
| 200501600000040 | 16 | 10 | 60 | 100 | 16 | 4.37 |
| 200502000000040 | 20 | 18.3 | 75 | 120 | 20 | 7.4 |