



Turnbuckle Eye/Eye Green Pin® G-6311

Product information

The Green Pin® EE Turnbuckle is a turnbuckle with eye-eye end-fittings, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EE Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 2 3/4" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

Material: Drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot dipped galvanized

Safety factor: 5:1

Part code	WLL ton	Thread	Take up inch	a "	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Weight kg	Delivery time
422100100250	1	1/2	6	1/2	325	455	193	12	18	36	58	0.81	10
422100100255	1	1/2	9	1/2	400	608	270	12	18	36	57	1.07	10
422100160250	1.59	5/8	6	5/8	380	503	203	14	21	45	79	1.33	10
422100160255	1.59	5/8	9	5/8	455	656	280	14	21	45	78	1.61	10
422100160256	1.59	5/8	12	5/8	531	808	356	14	21	45	78	1.96	10
422100240250	2.36	3/4	6	3/4	413	532	214	17	26	54	89	2.03	10
422100240255	2.36	3/4	9	3/4	490	685	291	17	26	54	89	2.47	10
422100450255	4.54	1	6	1	498	604	234	24	37	76	118	4.35	10
422100450256	4.54	1	12	1	649	909	387	24	37	76	117	5.75	2
422100690255	6.9	1 1/4	18	1 1/4	862	1,287	537	29	47	91	144	11.1	10
422100970250	9.71	1 1/2	12	1 1/2	756	1,023	401	32	55	106	156	14.2	10
422100970255	9.71	1 1/2	18	1 1/2	916	1,335	553	32	55	106	160	15.8	10
422100970256	9.71	1 1/2	24	1 1/2	1,065	1,636	706	32	55	106	158	17.1	10
422101680250	16.8	2	24	2	1,264	1,784	748	46	69	147	230	40.7	10

Blueprint

