



## Turnbuckle Hook/Hook Green Pin® G-6312

### Product information

The Green Pin® HH Turnbuckle is a turnbuckle with hook-hook end-fittings, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® HH Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread of 3/8" (take up of 6") up to 1" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

**Standard:** Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

**Material:** Drop forged high tensile steel SAE 1035 or 1045.

**Marking:** CE-marked

**Temperature range:** -20°C up to +200°C

**Finish:** Hot dip galvanized.

**Safety factor:** 5:1

Part code	WLL ton	Thread	Take up inch	a"	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg	Delivery time
422100540310	0.54	3/8	6	3/8	278	415	13	16	15	42	0.53	10
422100100310	1	1/2	6	1/2	305	434	16	22	16	48	0.93	10
422100450315	4.54	1	12	1	625	886	26	35	31	106	6.64	10

## Blueprint

