



Turnbuckle Jaw/Jaw Pin Green Pin® G-6313

Product information

The Green Pin® JJ Turnbuckle CP is a turnbuckle with jaw-jaw end-fittings and cotter pins, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® JJ Turnbuckle CP ensures its long-term durability. The turnbuckle is available in a range with a diameter thread of 3/4" (take up of 6") up to 2 3/4" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

Material: Drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot dipped galvanized

Safety factor: 5:1

Part code	Diameter mm	WLL ton	Thread Inch	Take up inch	a " mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	Weight kg	Delivery time
422100240260	41	2.36	3/4	6	3/4	369	487	439	24	38	16	16	41	2.59	10
422100240265	41	2.36	3/4	9	3/4	444	640	514	24	38	16	16	41	3.13	2
422100240266	41	2.36	3/4	12	3/4	520	792	590	24	38	16	16	41	3.42	10
422100240267	41	2.36	3/4	18	3/4	670	1,096	740	24	42	16	16	41	4.51	10
422100330260	48	3.27	7/8	12	7/8	561	826	638	27	42	19	19	48	4.93	10
422100330265	48	3.27	7/8	18	7/8	713	1,132	790	27	42	19	19	48	6.41	10
422100450265	54	4.54	1	6	1	447	554	532	31	93	22	20	54	5.18	10
422100450266	54	4.54	1	12	1	598	859	683	31	93	22	20	54	6.43	10
422100450267	54	4.54	1	18	1	750	1,168	835	31	93	22	20	54	8.4	10
422100450260	54	4.54	1	24	1	903	1,470	988	31	50	22	20	54	8.9	10
422100690265	68	6.9	1 1/4	12	1 1/4	641	914	748	44	71	29	26	68	11.2	10
422100690266	68	6.9	1 1/4	18	1 1/4	803	1,228	910	44	71	29	26	68	13.6	10
422100690260	68	6.9	1 1/4	24	1 1/4	962	1,539	1,069	44	71	29	26	68	15	10
422100970260	80	9.71	1 1/2	12	1 1/2	675	942	806	52	71	35	28	80	17	10
422100970265	80	9.71	1 1/2	18	1 1/2	825	1,244	956	52	76	35	28	80	19.3	10
422100970266	80	9.71	1 1/2	24	1 1/2	980	1,551	1,111	52	76	35	28	80	20.7	10
422101270260	90	12.7	1 3/4	18	1 3/4	938	1,316	1,092	60	86	41	33	90	25	10
422101270265	90	12.7	1 3/4	24	1 3/4	1,089	1,621	1,243	60	86	41	33	90	28.7	10
422101680260	107	16.8	2	24	2	1,151	1,671	1,338	63	93	51	40	107	45.4	10
422102720260	143	27.2	2 1/2	24	2 1/2	1,255	1,831	1,480	75	114	57	41	143	88	10
422103400260	158	34	2 3/4	24	2 3/4	1,348	1,882	1,604	90	110	70	41	158	98	10

Blueprint

