Lifting Solutions Group
Axel Johnson International

Lifting Chain Grade 8

Product information

Round link lifting chain Grade 8.

... *Read more*



Marking: According to standard, at least every 20th link, or at least one link per meter, is labeled with manufacturer, grade and traceability code.
Temperature range: -40°C up to +400°C
Finish: Black painted.
Standard: EN 818-2

Safety factor: 4:1
Grade: 8


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Lifting Chain Grade 8

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length mm	ø d mm mm	p mm	w1mm mm	w2 mm	Weight kg/m
203102200000080	22	15	608	66	22	66	28.6	81.4	10.93
203102600000080	26	21.2	849	78	26	78	33.8	96.2	15.1
203102800000080	28	25	985	84	28	84	36.4	104	18.24
203103200000080	32	31.5	1,290	96	32	96	41.6	118	22
203103600000080	36	40	1,630	108	36	108	46.8	133	28.1
203104000000080	40	50	2,010	120	40	120	52	148	36

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved