

Modular spreader - MOD 34

Product information

The standard range

Modular spreader beams provide the ideal solution for most lifting requirements – versatile and cost-effective. Modulift MOD 34 is available with capacity up to 34 t at 6 m and up to 10 m at a lower capacity.

[Click here to see the load v span chart for the standard range.](#)

The modular configuration and interchangeable components enable Modulift spreaders to be reused over many lifts. Designed by Modulifts engineering experts and manufactured in their own specialist facilities; the Modulift range are the leading modular spreader beams on the market.

How the spreader beam is configured

Every Modulift modular spreader beam consists of a pair of end units and a pair of drop links, with interchangeable struts that can be bolted into the assembly between the end units to either lengthen or shorten the beam to suit the requirements of the lift, making them reusable at different spans. The different components are shown in the table below. If you need help to configure your spreader beam, please contact us.

Load monitoring with Active Link

The innovative Active Link provides wireless real time data by measuring the load at either end of the spreader beam and is ideal for both weighing and dynamic load monitoring. Data is transmitted wirelessly to a USB transceiver that must be connected to a Windows computer or tablet with a spare USB port. The Active Link, which replaces the standard drop link component, offers myriad time, cost and weight advantages.

We can offer Modulift Heavy Spreader Beams up to 1000 t. Contact us for more info about these beams.



Part code	Type	Weight kg	Delivery time
62080034DL017	Drop Link WLL 17t	7	10
62080034050	0.50 m Strut	20	10
62080034EU017	End Unit WLL 17t	23	10
62080034100	1.0 m Strut	31	10
62080034200	2.0 m Strut	51	10
6208CMOD34	Set of 4 corners	-	10

Blueprint

