



Swivel Bearing Hoist Hook X-175N

Product information

- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

Material: Alloy steel - quenched and tempered

Marking: CE-marked, Batch number, grade, chain size

Finish: Blue painted.

Safety factor: 4:1

Grade: 10

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D, mm	G, mm	H, mm	K mm	L mm	Pmm mm	P1 mm mm	T mm mm	Weight kg	Delivery time
420500250920	CC	7-8	2.5	36	29	26	13	90	27	145	184	24	20	22	1	2
420500400920	DD	10	4	41	35	29	16	102	29	172	217	28	25	24	1.6	10
420500670920	EE	13	6.7	46	44	38	21	122	38	218	277	35	31	31	3.3	2
420501000920	FF	16	10	61	50	49	23	160	48	261	332	43	39	35	5.6	2
420501600920	GG	18-20	16	74	82	62	25	196	56	327	410	61	57	47	9.5	10
420501900920	HH	22	19	97	96	65	33	221	64	372	471	72	62	56	16	2
420502650920	JJ	26	26.5	123	116	71	51	277	76	469	599	86	81	68	33.5	2

Blueprint

