Swivel Bearing Hoist Hook X-175N

Product information



- 20,000 cycle fatigue rated to 1.5 times of 4:1 WLL
- All swivel hoist hooks are 100% magnaflux crack detected.
- Ball bearing performs fully swivel under load.

... *Read more*

Material: Alloy steel - quenched and tempered
Marking: CE-mark, Batch number, grade, chain size
Finish: Blue painted.

Safety factor: 4:1
Grade: 10


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Swivel Bearing Hoist Hook X-175N

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	G mm	H mm	K mm	L mm	P mm	P1 mm	T mm	Weight kg
420500250920	CC	7-8	2.5	36	29	26	13	90	27	145	184	24	20	22	1
420500400920	DD	10	4	41	35	29	16	102	29	172	217	28	25	24	1.6
420500670920	EE	13	6.7	46	44	38	21	122	38	218	277	35	31	31	3.3
420501000920	FF	16	10	61	50	49	23	160	48	261	332	43	39	35	5.6
420501600920	GG	18-20	16	74	82	62	25	196	56	327	410	61	57	47	9.5
420501900920	HH	22	19	97	96	65	33	221	64	372	471	72	62	56	16
420502650920	JJ	26	26.5	123	116	71	51	277	76	469	599	86	81	68	33.5

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved