

Ferrule T Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and spiral strand ropes.

... [Read more](#)

Material: Aluminum

Marking: According to standard

Standard: EN 13411-3

except size range

Note: See the manufacturer's product data sheet in the tab "Documents" for guidance on dimension selection.

Ferrule T Talurit®

Technical data

| Part code | Ferrule size | Length mm |
|--------------|--------------|-----------|
| 120100250020 | 2.5 | 12 |
| 120100300020 | 3 | 14 |
| 120100350020 | 3.5 | 16 |
| 120100400020 | 4 | 18 |
| 120100450020 | 4.5 | 20 |
| 120100500020 | 5 | 23 |
| 120100600020 | 6 | 27 |
| 120100650020 | 6.5 | 29 |
| 120100700020 | 7 | 32 |
| 120100800020 | 8 | 36 |
| 120100900020 | 9 | 40 |
| 120101000020 | 10 | 45 |
| 120101100020 | 11 | 50 |
| 120101200020 | 12 | 54 |
| 120101300020 | 13 | 59 |
| 120101400020 | 14 | 63 |
| 120101600020 | 16 | 72 |
| 120101800020 | 18 | 81 |
| 120102000020 | 20 | 90 |
| 120102200020 | 22 | 99 |
| 120102400020 | 24 | 108 |
| 120102600020 | 26 | 117 |
| 120102800020 | 28 | 126 |
| 120103000020 | 30 | 135 |
| 120103200020 | 32 | 144 |
| 120103400020 | 34 | 153 |
| 120103600020 | 36 | 162 |
| 120103800020 | 38 | 171 |
| 120104000020 | 40 | 180 |
| 120104200020 | 42 | 189 |
| 120104400020 | 44 | 198 |

Ferrule T Talurit®

Technical data

| Part code | Ferrule size | Length mm |
|--------------|--------------|-----------|
| 120104600020 | 46 | 207 |
| 120104800020 | 48 | 216 |
| 120105000020 | 50 | 225 |
| 120105200020 | 52 | 234 |
| 120105400020 | 54 | 243 |