Dynamometer Tractel® Dynafor® Industrial

Product information



Rugged and lightweight wireless digital dynamometer. Integrated LCD screen with 18 mm high digits for good readability. With indication of battery discharge status. With tare, peak hold and units change (kg, daN, lbs), automatic zeroing, automatic stop without load or variation (20 min.).

Specifications:

- Capacity range from 1 t up to 20 t
- ±0.3% accuracy of measuring range
- Battery life: 350 h
- Uses 2 x AAA batteries

Protection class: IP65

... *Read more*

Material: Steel, aluminium
Temperature range: -20°C up to +50°C


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Dynamometer Tractel® Dynafor® Industrial

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
423500100110	1	191	164	22	83.5	22	19.8	36.4	37.6	0.75
423500320110	3.2	191	164	22	99.5	22	19.8	36.4	44.8	0.93
423500630110	6.3	236	184	28	121.5	22	19.8	36.4	54.7	1.44
423501250110	12.5	277	226	42	120.5	45	40.5	59.4	60	3.22
423502000110	20	342	264	54	147	45	40.5	59.4	73.5	5.1

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved