Lifting Solutions Group
Axel Johnson International

Rigging Screw Gunnebo No. 801 Jaw-Jaw

Product information

Standard: Working load acc. to U.S. Fed.spec.FF-T-791.b. Supplied with closed body from 2,5-17 T, larger dimensions open body.

... *Read more*



Material: Quenched and tempered alloy steel.
Temperature range: -20°C up to +200°C
Finish: Hot dip galvanized.

Safety factor: 5:1


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Rigging Screw Gunnebo No. 801 Jaw-Jaw

Blueprint



Technical data

Part code	WLL ton	Thread mm	Tensioning length	B mm	F mm	G mm	H mm	K mm	L mm	M mm	N mm	Weight kg
422100250360	2.5	M20	210	270	13	21	45	20	16	50	455	2.3
422100500360	5	M24	250	340	19	28	56	28	22	65	570	4.6
422100700360	7	1 1/4"	270	370	22	35	70	38	28	85	680	8
422101000360	10	1 1/2"	300	400	25	40	78	45	32	100	790	14
422101300360	13	1 3/4"	360	500	30	45	90	50	39	105	870	24
422101700360	17	2"	450	600	35	45	100	58	45	120	1,030	38

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved