Lifting Solutions Group
Axel Johnson International

Syntethic Lifting Chain Murlink®

Product information



The Murlink® synthetic lifting chain is a soft and strong chain, made from the world's strongest man-made fiber Dyneema®.

Properties:

- Soft, strong, silent and light
- Made from Dyneema®
- Extremely resistant to chemicals, abrasion and cuts
- Minimizes damage to cargo and persons
- Floats on water
- Safe to work with
- Increases efficiency and productivity
- Adjustable length at each link

Fully approved and certified by Applus+ and complies with Machine Directive 2006/42/EC

... *Read more*

Material: UHMWPE Fiber
Marking: CE-mark, Manufacturer ID, WLL, traceability code
Temperature range: -20ºC up to +70ºC

Safety factor: 4:1

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Syntethic Lifting Chain Murlink®

Technical data

Part code	WLL ton	MBL ton	Link size mm	Weight kg
2098323008	8	32	125	0.94
2098423010250	10.5	42	250	1.05
2098644012	16	64	250	1.749
2098724013	18	72	250	1.904

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved