Lifting Solutions Group
Axel Johnson International

Verolube Spray

Product information



Verolube Spray is used for lubrication and is a very fluid rope lubricant. It penetrates well into the cable strands and provides corrosion protection, wear protection, water resistance, weather resistance and adhesion.
The wire rope lubricant has two major tasks: it should protect the rope from corrosion and it should minimize the friction between the rope elements themselves and between the rope and the sheave or the drum. A reduction of the friction reduces the actuating power and minimizes the wear of the rope, the sheaves and the drums. We differentiate between wax-based lubricants and oil-based lubricants. While wax-based lubricants offer a better handling of the ropes, the oil-based lubricants advantage is a better closing of the lubrication film due to the gravitational force of the oil. The quality of the wire rope lubricant has a great impact on the fatigue resistance of a wire rope

Packaging: Spray can 600 ml.
Colour: Black
Due to oil: Min
Fixed lubricants: C

... *Read more*

Temperature range: -35 up to +65°

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Verolube Spray

Technical data

Part code	Description
142540000102	Spray

Designation	Value
Colour	Black
Service temperature range	-35/+65°
Due to oil	Min
Fixed lubricants	C
DIN Regulation	LLS 134

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved