Lifting Solutions Group
Axel Johnson International

Chain DIN 766A

Product information

Use for anchorchain, barrier, insurance against burglary, common non-lifting assignments.

Breaking loads are estimated ratings.

... *Read more*



Material: Not calibrated.
Marking: According to standard
Finish: Hot dip galvanized as standard. Also available as untreated on request.
Standard: DIN 766
Note: As standard in bundles a 50 m.
Warning: Not for lifting.

Grade: 3


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain DIN 766A

Blueprint



Technical data

Part code	Chain diameter mm	Min. breaking force kN	Package	D mm	E mm	H mm	Weight kg/m
200500400000081	4	5.88	Bundle	4	16	6	0.32
200500500000081	5	12.35	Bundle	5	18,5	7	0.5
200500600000081	6	17.65	Bundle	6	18,5	8	0.75
200500700000081	7	24.71	Bundle	7	22	9	1
200500800000081	8	31.38	Bundle	8	24	10	1.35
200501000000081	10	49	Bundle	10	28	14	2.25
200501200000081	12	68.64	Bundle	12	36	16	3.1
200501600000081	16	123.56	Bundle	16	45	22	5.8
200502000000081	20	196	Bundle	20	56	27	9

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved