Lifting Solutions Group
Axel Johnson International

Insulated Swivel 8-088N

Product information



Insulated blank swivel for various lifting applications. Design for protection of overhead crane during welding operations on suspended loads. Individually tested to resist 1000 Volts insulated with Test Certificate.

For connection with suspension parts you will need Coupling Pin and C-Sleeve Set X-P015, please order them separately.

Order suspension parts Coupling Master Link 8-051.

2 pcs. half coupling links can be ordered as 1 pc. X-015 + 1 pc. X-P015.
Other suspension parts on request.

... *Read more*

Features: Built-in RFID/NFC chip
Material: Quenched and tempered alloy steel
Marking: According to standard
Standard: EN 1677-1

Safety factor: 4:1
Grade: 8


CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Insulated Swivel 8-088N

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	D mm	L mm	W mm	Weight kg
422500200220	7-8	2	48	75	50	0.7
422500320220	10	3.15	58	97	62	1.3
422500530220	13	5.3	74	123	78.5	2.7
422500800220	16	8	90	143	95	4.7
422501250220	18-20	12.5	105	164	110	7

CERTEX Danmark A/S
info@certex.dk
+45 74 54 14 37
© November 2026 - All Rights Reserved