

Unilock Connecting Link U Pewag

Product information



U Unilock connecting links are designed for the assembly of pewag chain slings. Special accessory in grade 8. UB bolts, UM safety nut and US washers are also separately available.

General connecting link for:

Master link - chain or rope, hook - chain or rope, chain - various securing eyes. Always ensure that the nut is not overtightened and that the bolt can rotate. Cannot be assembled to PW (PSW).

... [Read more](#)

Material: High duty grade 8.

Marking: According to standard, CE-marked

Temperature range: -40°C up to +100°C.

Finish: Red powder coated.


Standard: EN 1677-1

Safety factor: 4:1

Grade: 8

Unilock Connecting Link U Pewag

Blueprint



Technical data

Part code	Code	WLL ton	a mm	b mm mm	dmm mm	e mm mm	Mmm mm	smm mm	Weight kg
401200110060	U 5/6	1.12	16	21	9	34	7	11	0.07
401200150060	U 7	1.5	22	28	13	49	8	16	0.2
401200200060	U 8	2	22	28	13	48	10	16	0.22
401200320060	U 10	3.15	27	35	16	60	12	20	0.38
401200530060	U 13	5.3	34	39	18	72	16	24	0.67
401200800060	U 16	8	44	47	23	80	20	32	1.21
401201250060	U 19/20	12.5	52	56	26	96	24	36	1.97
401202120060	U 26	21.2	66	77	33	132	30	49	4.06