# Unilock Connecting Link U Pewag

**Product information**



U Unilock connecting links are designed for the assembly of pewag chain slings.
Special accessory in grade 8.
UB bolts, UM safety nut and US washers are also separately available.

**General connecting link for:**
Master link - chain or rope, hook - chain or rope, chain - various securing eyes.
Always ensure that the nut is not overtightened and that the bolt can rotate.
Cannot be assembled to PW (PSW).

... *Read more*

**Material:** High duty grade 8.
**Marking:** According to standard, CE-mark
**Temperature range:** -40ºC up to +100°C.
**Finish:** Red powder coated.
**Standard:** EN 1677-1

**Safety factor:** 4:1
**Grade:** 8


**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Unilock Connecting Link U Pewag

## Blueprint




## Technical data

| Part code | Code | WLL ton | a mm | b mm | d mm | e mm | M mm | s mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|
| 401200110060 | U 5/6 | 1.12 | 16 | 21 | 9 | 34 | 7 | 11 | 0.07 |
| 401200150060 | U 7 | 1.5 | 22 | 28 | 13 | 49 | 8 | 16 | 0.2 |
| 401200200060 | U 8 | 2 | 22 | 28 | 13 | 48 | 10 | 16 | 0.22 |
| 401200320060 | U 10 | 3.15 | 27 | 35 | 16 | 60 | 12 | 20 | 0.38 |
| 401200530060 | U 13 | 5.3 | 34 | 39 | 18 | 72 | 16 | 24 | 0.67 |
| 401200800060 | U 16 | 8 | 44 | 47 | 23 | 80 | 20 | 32 | 1.21 |
| 401201250060 | U 19/20 | 12.5 | 52 | 56 | 26 | 96 | 24 | 36 | 1.97 |
| 401202120060 | U 26 | 21.2 | 66 | 77 | 33 | 132 | 30 | 49 | 4.06 |

**CERTEX Danmark A/S**
info@certex.dk
+45 74 54 14 37

© November 2026 - All Rights Reserved